



Schieß- und Splitterschutzvorhänge

RUTEC® Projectionpaper 190g/m² (1480)

TECHNICAL SPECIFICATIONS

| | |
|---|------------------------------|
| Grammage (ISO 536) | 190 g/m ² (± 5 %) |
| Tensile strength along (ISO 1924-2) MD | 16 kN/m |
| Tensile strength transverse (ISO 1924-2) CD | 7 kN/m |
| Tensile strength longitudinal (ISO 1974) MD | 2,2 N |
| Tear resistance transverse (ISO 1974) CD | 2,3 N |
| Bursting pressure (ISO 2758) | 620 kPa |

STANDARD VERSIONS

| | |
|------------------|-------------------------|
| Roll width | 1.440 mm - 2.640 mm |
| Roll length | 100 lfm |
| Housing diameter | 70 mm |
| 2 Notches | 15 mm breit, 40 mm tief |

Information given here represents our experience. There are no specifications. Before using our products, please check whether they are suitable for the purpose intended by you individually.



Download the Datasheet as PDF



www.rutec-gummi.com

RUTEC® a Brand of:

SGP Spezial Gummi Produkte GmbH

Raiffeisenstr. 37 · D - 46244 Bottrop · T. +49 (0) 20 45 / 414 16-0



Premium Rubber Quality